



REFINED PRODUCTS

Refined Products

100 Sonneborn Lane, Petrola, PA. 16050-1410

Technical Service: 1-877-541-7144

SPECIFICATIONS FOR COMPRESSOR LUBRICANT 1000 PHLA 3.0

PROPERTIES GUARANTEED	TEST METHOD	LIMITS
SPECIFIC GRAVITY @ 25°C	ASTM D4052	0.859/0.886
VISCOSITY @ 40°C, CST	ASTM D445	178/209
NEUTRALIZATION NO., mg KOH/g	ASTM D974	5.4/7.8
FLASH POINT, COC, °C	ASTM D92	218 Min.
WATER, ppm	ASTM D1533	60 Max.
ODOR	SMELL	SLIGHT POLYBUTENE
APPEARANCE	VISUAL	PASS

TYPICAL PROPERTIES FOR COMPRESSOR LUBRICANT 1000 PHLA 3.0

PROPERTIES	TEST METHOD	TYPICAL VALUE
SAYBOLT COLOR	ASTM D156	+25

No warranties, express or implied, including patent warranties or warranties of merchantability or fitness for a particular use, are made by Crompton Corporation with respect to any products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent. All sales are subject to Crompton Corporation's standard terms and condition of sale.

0308011361

13223