

Specifications for
HYDROBRITE® 380 PO White Mineral Oil

PROPERTIES GUARANTEED	TEST METHOD	LIMITS
SPECIFIC GRAVITY @ 25°C/25°C	ASTM D4052	0.860/0.873
KIN. VISCOSITY @ 40°C, cSt	ASTM D445	70/90
NEUTRALITY	USP (current revision)	PASS
READILY CARBONIZABLE SUBSTANCES	USP (current revision)	PASS
SOLID PARAFFIN	USP (current revision)	PASS
LIMIT OF POLYNUCLEAR COMPOUND	USP (current revision)	PASS
SULFUR COMPOUNDS	USP XVII	PASS
ODOR	LATM 092	NONE
COLOR, SAYBOLT	ASTM D156	30 Min.
GC DISTILLATION, 5%, °C	ASTM D2887	415 Min.
SMOKE POINT, °C	LATM 141	138 Min.
POUR POINT, °C	ASTM D97	- 9 Max.
FLASH POINT, COC, °C	ASTM D92	240 Min.
REFRACTIVE INDEX@ 25°C	ASTM D1218	1.472/1.478

HYDROBRITE 380 PO is a Mineral Oil USP meeting requirements for USP (current revision) and FDA requirements as per 21 CFR 172.878 and 21 CFR 178.3620(a).

Supplemental Properties For HYDROBRITE 380 PO White Mineral Oil
Not Guaranteed or Reported on Certificate Of Analysis

Supplemental Properties	Test Method	Typical	EU Limits
Saybolt Viscosity @ 100°F, SUS	ASTM D2161	407	N/A
Paraffinic Carbon, %	ASTM D3238	68.9	N/A
Kinematic Viscosity @ 25°C, cSt	ASTM D341	171	N/A
D 1160 DIST. @ 10 mm Hg, 2.5%, °C	LATM 140	284	N/A
Kinematic Viscosity @ 100°C, cSt	ASTM D445	9.66	8.5 min.
Average Molecular Weight	ASTM D2502	503	480 min.
Carbon Number at 5% Distillation Point	ASTM D2887	> 26	25 min.