

Product name: PETRONATE® H Sodium Sulfonate

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PETRONATE® H Sodium Sulfonate

Chemical name: Oil Soluble Sodium Sulfonate

Supplier: Sonneborn, Inc.
575 Corporate Drive, Suite 415
Mahwah, NJ 07430 USA

Emergency telephone number: CHEMTREC (24 hours) 800-424-9300
Sonneborn, Inc. Emergency Response
(24 hours) 724-756-2210

For MSDS, Product Safety, or regulatory inquiries, call: 877-948-2688

Customer Service: 877-948-2688

2. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS#	CONCENTRATION
Sodium Sulfonate	68608-26-4	50.0 - 65.0 %

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW
CAUSES EYE IRRITATION.

CAUSES SKIN IRRITATION.

4. FIRST AID MEASURES

Swallowing

Do not induce vomiting. Rinse mouth with water. Obtain medical attention.

Skin

Remove contaminated clothing. Wash thoroughly with warm water using a mild soap. Obtain medical attention if irritation persists.

Inhalation

Remove to fresh air. Obtain medical attention.

Eye contact

Product name: PETRONATE® H Sodium Sulfonate

Immediately flush eyes with water and continue washing for several minutes. Obtain medical attention if irritation persists.

5. FIRE-FIGHTING MEASURES

Flash point: > 180 °C (> 350 °F)

NFPA CLASSIFICATION

Health: 2	Flammability: 1	Reactivity: 0	Special provisions: -
-----------	-----------------	---------------	-----------------------

Special fire fighting procedures

Do not discharge extinguishing waters into streams, rivers and lakes.

Special protective equipment for firefighters

Body covering protective clothing, full "turn-out" gear. Self-contained breathing apparatus.

Extinguishing media

Suitable: Large fires:
- alcohol-type foam or universal-type foams
Small fires:
- CO2
- dry chemical

Unsuitable: - water jets

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear suitable protective equipment. Avoid contact with eyes and skin.

Environmental precautions

Prevent from entering sewer system, surface water or soil.

Methods for cleaning up

Observe government regulations.

Small spills Absorb on inert material such as sand, earth, vermiculite.
Collect for disposal.

Large spills Dike to contain spill.
Pump excess material into suitable container (metal drums, metal tank, or such).

Product name: PETRONATE® H Sodium Sulfonate

7. HANDLING AND STORAGE

HANDLING

Handling precautions

Do not get in eyes. Avoid prolonged or repeated contact with skin. Avoid breathing vapor. Use with adequate ventilation. Wash thoroughly after handling.

STORAGE

Storage requirements

Store in a cool, dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION

Respiratory protection

Self-contained breathing apparatus in high vapor concentrations.

Hand protection / protective gloves

Chemical resistant protective gloves

Eye protection

Safety glasses with side shields.

Skin protection

Wear protective clothing, such as long sleeves to minimize skin contact.

Other protective equipment

Eye bath

Safety shower

ENGINEERING CONTROLS

Ventilation

General (mechanical) room ventilation is expected to be satisfactory.

Special, local ventilation is needed at points where vapors can be expected to escape to the workplace air.

EXPOSURE LIMITS

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Remark</u>
Mineral Oil Mist	TWA (mist), ACGIH	5.0 mg/m ³	If used in way that generates a "mist" observe the limits for Mineral Oil Mist.
	STEL (mist), ACGIH	10.0 mg/m ³	

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Physical state

Viscous liquid

Product name: PETRONATE® H Sodium Sulfonate

Color Brown
Odor Mild petroleum

OTHER PROPERTIES

Boiling point 100 °C at STP unless specified below.
water present

Specific gravity (H₂O=1) > 1 at 16 °C

Vapor pressure Negligible

Solubility in water May emulsify

Solubility in organic solvents Partially soluble

Partitioning coefficient No data available.

Flash point > 180 °C (> 350 °F)
Method: Cleveland open cup ASTM D 92

Percent volatiles < 5 %(m)
Water.

Kinematic viscosity > 30 mm²/s at 40 °C

10. STABILITY AND REACTIVITY

Stability: This product is stable under normal storage and handling conditions.

Incompatible materials

Strong acids.
Strong bases.
Oxidizing agents.

Hazardous combustion products

Irritating fumes.
Oxides of carbon.
Oxides of nitrogen.

Hazardous polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

SWALLOWING

Chronic effects
No data available.

Product name: PETRONATE® H Sodium Sulfonate

Test results

Acute toxicity:

LD50 - Rat

Result: > 6,000 mg/kg

Remark: Test results are based on analogy with a similar material.

SKIN CONTACT

Acute effects

May cause irritation.

EYE CONTACT

Acute effects

Causes irritation.

12. ECOLOGICAL INFORMATION

No information available.

_____nrsid6816725

13. DISPOSAL CONSIDERATIONS

General: Dispose of in accordance with appropriate Federal, State, and local regulations. Avoid discharge to sewers and natural waters.

Non-cleaned packages

Empty drums should be decontaminated and either passed to an approved drum reconditioner or destroyed. Containers that cannot be cleaned must be treated as waste.

14. TRANSPORT INFORMATION

DOT Classification

Not regulated by ground or rail if shipped or transported at temperatures under 212 °F (100 °C) or in containers less than 450 liters (119 US gal). If shipped or transported at temperatures over 100°C (212°F) and in containers greater than 450 liters (119 gal) regulated as: ELEVATED TEMPERATURE LIQUID, N.O.S., Class 9, UN 3257, PGIII, ERG 128.

Freight description road: 65 PETROLEUM OIL, N.O.I.B.N

IMDG Classification

This product is not regulated by IMDG.

ICAO Classification

This product is not regulated by ICAO.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of

Product name: PETRONATE® H Sodium Sulfonate

annual reports of release of toxic chemicals that appear in 40CFR372 (for SARA 313). This information must be included in MSDS's that are copied and distributed for this material.

Components present in this product at a level which could require reporting under the statute are:

This product does not contain any chemical listed in Section 313 at or above de minimis concentrations.

New Jersey Worker and Community Right-To-Know Act (Labeling Requirements)

Chemical name
Sodium Sulfonate

CAS#
68608-26-4

New Jersey TS Number

EPA Hazard Categories (SARA 311, 312): None

CHEMICAL INVENTORY

Canada: The ingredients of this product are on the DSL.

Europe: The ingredients of this mixture are on the EINECS inventory.

United States: The ingredients of this product are on the TSCA inventory.

Australia: The ingredients of this product are on the AICS inventory.

China: This product is on the IECSC Inventory.

Japan: The ingredients of this product are on the ENCS inventory.

Korea: The ingredients of this product are on the ECL.

Philippines: The ingredients of this product are on the PICCS.

16. OTHER INFORMATION

FURTHER INFORMATION

MAY BE ON THE INVENTORY LIST BUT NOT NECESSARILY REGISTERED, (Korea, China, New Zealand) CONSULT REGULATORY SPECIALIST.

HMIS RATING

Health: 2	Flammability: 1	Reactivity: 1	PPI: -
-----------	-----------------	---------------	--------

LEGEND

STP	Standard temperature and pressure
W/W	Weight/Weight
0 (HMIS)	Minimal hazard
1 (HMIS)	Slight hazard
2 (HMIS)	Moderate hazard
3 (HMIS)	Serious hazard
4 (HMIS)	Severe hazard
X (HMIS)	Personal protection rating to be supplied by user depending on use conditions

Product name: PETRONATE® H Sodium Sulfonate

Copyright 2005 Sonneborn, Inc.

The opinions expressed herein are those of qualified experts within Sonneborn Inc.. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and of these opinions and the conditions of use of this product are not within the control of Sonneborn Inc., it is the user's obligation to determine the conditions of safe use of the products.